

NRS18P

16 Port gigabit POE+ unmanaged Switch with 2 GB SFP uplink ports



NRS26P

24 Port gigabit POE+ unmanaged Switch with 2 GB SFP uplink ports

FEATURES

Full Gigabit network ports

All ports on the NRS18P/NRS26P offer IEEE 802.3x full-duplex flow control and Backpressure half-duplex flow control.

PoE+ Power Supply

The RJ45 ports offer PoE+ to support the power supply needs of security, teleconferencing systems, wireless network coverage and other applications. Fully compliant with the IEEE 802.3af/at PoE power supply standards, the maximum PoE output power of the whole machine is 200W for the NRS18P and 300W for the NRS26P, the maximum PoE output power of PoE port is 30W. It automatically identifies PoE devices for power supply without damaging non-PoE devices.

Stable and reliable

The devices are designed for maximum stability, with the metal housing with electrostatic paint and double-flow heat dissipation.

It supports port surge protection: Common Mode 4KV, Differential Mode 2KV (Class B), ESD: Air 8KV, Contact 6KV (Class C).

One-Key Vlan isolation and 250 Meters PoE power

A simple dip-switch offers extended functionality of VLAN/port isolation and extended transmission range, up to 250M.

SPECIFICATIONS

	NRS18P	NRS26P
<i>Standard</i>	IEEE802.3 (Ethernet), IEEE802.3u (Fast Ethernet), IEEE802.3ab (Gigabit Ethernet), IEEE802.3x (Flow Control), IEEE 802.3z (Gigabit Ethernet Fiber Standard), IEEE 802.3af, IEEE 802.3at	
<i>Interface</i>	16*10/100/1000Mbps RJ45 PoE ports	24*10/100/1000Mbps RJ45 PoE ports
	2*Gigabit SFP ports	2*Gigabit SFP ports
	1* DIP switch (On/Off mode)	
	1 *AC input, 100~240V 50/60Hz	
<i>PoE Standard</i>	IEEE802.3af(15.4W) IEEE802.3at(30W) POE port output voltage: DC 44~57V POE power supply core: 1/2+; 3/6-	
<i>PoE Input</i>	52V /3.84A 200W	52V 7.69A 300W
<i>Power</i>	POE power: maximum 180W	POE power: maximum 300W
<i>Network Media</i>	10Base-T: Cat 3, 4, 5 Class or above UTP/STP (≤ 100m) 100Base-TX: Cat 5 Class or above UTP/STP (≤ 100m) 1000Base-TX: Cat 5 Class or above UTP/STP (≤ 100m)	
<i>Optical Medium</i>	Multimode optical fiber: 50/125, 62.5/125, 100/140um Single-mode optical fiber: 8/125, 8.7/125, 9/125, 10/125um	
<i>Bandwidth</i>	40Gbps	52Gbps
<i>Packet Forwarding Rate</i>	26.76Mpps	38.68Mpps
<i>Memory cache</i>	4Mbit	4Mbit
<i>MAC address table</i>	8K	
<i>Storage and forwarding</i>	Support	
<i>Working Environment</i>	Working Temperature: -10°C ~ 50°C Storage Temperature: -40°C ~ 70°C Working Humidity: 10% ~ 90% RH No-condensing Storage Humidity: 5% ~ 95% RH No-condensing	
<i>Size</i>	440*204*44mm	440*204*44mm
<i>LED Indicator Status</i>		
<i>LED Indicator</i>	PWR(Power), 1-18/26 Green Light(Link&Data), 1-18/20(Yellow Light), POE Led Key	

<i>PWR</i>	On: Powered on Off: Powered off
<i>1-18/26 Green Light (Link&Data)</i>	On: Link normal Off: Link blocked Flashing: Data transmitting
<i>1-16/24 (Yellow Light)</i>	On : POE power supply is normal Off : POE not powered
<i>PoE Max POE power light (Green Light)</i>	Off: indicates PoE power usage is less than 90% Flashing: indicates PoE power usage of $90\% \leq P \leq 95\%$ On: indicates that PoE power is used at $95\% < P < 100\%$
<i>Mode DIP Switch light</i>	On : Extend on Off : Extend off
<i>PoE Led Key</i>	Dual color light selection: default green (link data), switch yellow light (PoE)
<i>Extend DIP Switch</i>	OFF : common mode, all interfaces can communicate with each other, the transmission distance is less than 100 meters, the transmission rate is 10/100/1000M adaptive; The port AI mode is disabled ON: Link extension mode, 9-16/17-24 ports force 10M, link 250M (enable POE watchdog),Port AI mode is enabled.



WHO IS NIVEO PROFESSIONAL?

- ⚙️ Manufacturer of AV-Centric Networking Equipment
- 💡 Pioneer in the AV-Industry
- ***** 20 Years of AV-Centric Innovation!
- 🌐 Support around the globe, Delivery around the globe

**WE MAKE
NETWORKING
EASY!**

**AV-Centric
Switches**



**AVB/Milan
Switches**



**Power
Products**



**Wireless &
Routers**



Accessories



Niveo Professional

Olympia 2D, 1213NT, Hilversum, The Netherlands |
☎️ +31 (0) 85 060 4566 | ✉️ info@niveoprofessional.com
💻 www.niveoprofessional.com